



# SINGLE-PORT SYNCHRONOUS SERIAL MINI-PHYSICAL INTERFACE MODULE (MINI-PIM)

## Product Overview

Providing the physical connection to serial network media types, Juniper's single-port synchronous serial Mini-PIM is used for the Juniper Networks SRX200 line consisting of the SRX210 Services Gateway, SRX220 Services Gateway, and SRX240 Services Gateway products.

## Product Description

The Juniper Networks® single-port synchronous serial Mini-PIM provides the physical connection to serial network media types, receiving incoming packets from the network and transmitting outgoing packets to the network. The single-port synchronous serial Mini-PIM forwards packets for processing while performing framing and line-speed signaling.

## Features and Benefits

The Juniper Networks single-port synchronous serial Mini-PIM provides increased bandwidth capabilities while making effective use of the SRX200 line interface slots.

Features include:

- 60-pin synchronous serial (female) connector type
- Support for the following standards: TIA/EIA 530, V.35, X.21, RS-232, RS-449
- Up to 8 Mbps per physical port
- Clock rate configurable
- Crypto resynchronization support
- Juniper's proprietary data terminal equipment (DTE) and data circuit-terminating equipment (DCE) cables available for each protocol (10 in all) with auto-detection for DTE/DCE modes

## Specifications

### Interface Specifications

- Transmit rate: 8 Mbps per port
- Receive bit rate: 8 Mbps per port
- Line encoding: NRZ, NRZI
- Line protocols: EIA530, X.21, RS449/RS422, RS232, V35
- Modes: DTE, DCE

### Data Interface

- Data interface Point-to-Point Protocol (PPP)
- Frame Relay
- High-Level Data Link Control (HDLC) features
  - 56 K/64 K mode
  - Cyclic redundancy check (CRC)16/32
  - Shared flag
  - Idle flag/fill
  - Counters: Runts, giants, fcs error, abort error, align error

**Table 1: Interface Connector**

PRODUCT NUMBER	TYPE	LENGTH	CONNECTOR TYPE
JX-CBL-EIA530-DCE	EIA530 cable (DCE)	10 feet	Female
JX-CBL-EIA530-DTE	EIA530 cable (DTE)	10 feet	Male
JX-CBL-RS232-DCE	RS232 cable (DCE)	10 feet	Female
JX-CBL-RS232-DTE	RS232 cable (DTE)	10 feet	Male
JX-CBL-RS449-DCE	RS449 cable (DCE)	10 feet	Female
JX-CBL-RS449-DTE	S449 cable (DTE)	10 feet	Male
JX-CBL-V35-DCE	V.35 cable (DCE)	10 feet	Female
JX-CBL-V35-DTE	V.35 cable (DTE)	10 feet	Male
JX-CBL-X21-DCE	X.21 cable (DCE)	10 feet	Female
JX-CBL-X21-DTE	X.21 cable (DTE)	10 feet	Male

### System Timing

- Clocking Modes: DCE, internal, loop
- Clocking Rates: 1.2 KHz, 2.4 KHz, 9.6 KHz, 19.2 KHz, 38.4 KHz, 56.0 KHz, 64.0 KHz, 72.0 KHz, 125.0 KHz, 148.0 KHz, 250.0 KHz, 500.0 KHz, 800.0 KHz, 1.0 MHz, 1.3 MHz, 2.0 MHz, 4.0 MHz, 8.0 MHz

### Dimensions and Weight (W x H x D)

- 3.75 x 0.8 x 5.9 in (9.5 x 2.0 x 14.5 cm)
- 0.19 lb

### Environmental

- Operating temperature: 0° to 40° C
- Storage temperature: -40° to 70° C
- Relative humidity: 5% to 90% noncondensing

### Diagnostics

#### Loopbacks

- Local, DCE-local

#### Network Alarms

- Rx clock absent
- Tx clock absent
- Data carrier detect (DCD) absent
- Clear to send (CTS) absent
- Data set ready (DSR) absent

#### Error Counters

- Controlled slipped seconds (CSS or CS)
- Line errored seconds (LES)
- Errored seconds (ES)
- Bursty errored seconds (BES)
- Severely errored seconds (SES)
- Severely errored framing seconds (SEFS)
- Loss of signal seconds (LOS)
- Loss of frame seconds (LOFS)
- Unavailable seconds (UAS)

### LEDs

Mini-PIM LEDs indicate port status with the following LED states:

- Green on means that the port is online with no alarms or failures
- Red light on means that the port is active with a local alarm (router has detected a failure)

### Management Capabilities

- Telnet/console/Juniper Networks J-Web Software: Remote and local configuration, monitoring, and troubleshooting

### Standards and Compliance

#### Safety

- CAN/CSA-C22.2 No. 60950-1
- UL 60950-1
- EN 60950-1
- IEC 60950-1

#### EMC (Emissions)

- AS/NZS CISPR22 Class B
- EN55022 Class B
- FCC Part 15 Class B
- VCCI Class B

#### Immunity

- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity

### European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2 Telecommunication Network Equipment Electromagnetic Compatibility

### Standards

- ITU V.35
- ITU X.21
- EIA/TIA 530
- EIA/TIA 232
- EIA/TIA 422

### Juniper Networks Services and Support

Juniper Networks is the leader in performance-enabling services and support, which are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to bring revenue-generating capabilities online faster so you can realize bigger productivity gains and faster rollouts of new business models and ventures. At the same time, Juniper Networks ensures operational excellence by optimizing your network to maintain required levels of performance, reliability, and availability. For more details, please visit [www.juniper.net/us/en/products-services/](http://www.juniper.net/us/en/products-services/).

## Ordering Information

PART NUMBER	DESCRIPTION
SRX-MP-1SERIAL	Single-port Sync Serial Mini-PIM

## Software

The single-port synchronous serial Mini-PIM is supported on the SRX200 line running Juniper Networks Junos® operating system 9.5 and higher releases.

## About Juniper Networks

Juniper Networks, Inc. is the leader in high-performance networking. Juniper offers a high-performance network infrastructure that creates a responsive and trusted environment for accelerating the deployment of services and applications over a single network. This fuels high-performance businesses. Additional information can be found at [www.juniper.net](http://www.juniper.net).

---

**Corporate and Sales Headquarters**

Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, CA 94089 USA  
Phone: 888.JUNIPER (888.586.4737)  
or 408.745.2000  
Fax: 408.745.2100  
[www.juniper.net](http://www.juniper.net)

**APAC Headquarters**

Juniper Networks (Hong Kong)  
26/F, Cityplaza One  
1111 King's Road  
Taikoo Shing, Hong Kong  
Phone: 852.2332.3636  
Fax: 852.2574.7803

**EMEA Headquarters**

Juniper Networks Ireland  
Airside Business Park  
Swords, County Dublin, Ireland  
Phone: 35.31.8903.600  
EMEA Sales: 00800.4586.4737  
Fax: 35.31.8903.601

To purchase Juniper Networks solutions, please contact your Juniper Networks representative at 1-866-298-6428 or authorized reseller.

Copyright 2010 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, Junos, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.